Dane aktualne na dzień: 13-11-2026 02:36

Link do produktu: https://www.sprzetspadochronowy.pl/c-mode-cypres-2-p-199.html



C-MODE CYPRES 2

Cena	**5 200,00 zł**

Opis produktu

The 4 in 1 solution providing more application possibilities than any other AAD.
This feature can be accomplished by a set series of control unit button pushes until the appropriate model can be selected.
The setting procedures is specially designed to make unwanted changes impossible.
The current model / setting version is visually recognizable on the control unit display when the unit is on.

Cable length of control unit:	approx. 650 mm
Volume:	approx. 139 cm³
Weight:	approx. 198 grams
Activation altitude:	according to set MODE
Activation speed:	according to set MODE
Length, width, height of the processing unit:	approx. 85 x 43 x 32 mm
Length, width, height of the control unit:	approx. 65 x 18 x 6.5 mm
Length, diameter of the release unit:	approx. 43 x 8 mm
Cable length of the release unit (including release unit):	approx. 500 mm
Storage temperature:	+71° to -25° Celsius
Storage pressure:	200 to 1094 hPa (5.906 to 32.306 In.Hg)
Working temperature:	+63° to -20° Celsius*
Maximum allowable humidity:	up to 99.9 % rel. humidity
Waterproof:	up to 24 hours down to a depth of 8 feet (2.5 meters)
Dropzone offset adjustment limits:	±3000 feet or ±1000 m
Operating range below / above sea level:	-2140 feet to +26,000 feet (-650 m to +8000 m)
Functioning period:	14 hours from switch-on
Power supply:	service life warranty**
Maintenance:	For units with DOM 12/15 and earlier the maintenance is mandatory to be performed 4 and 8 years after the original DOM. For units made in 2016 the maintenance is recommended to be performed 4 and 8 years after original DOM. For units with DOM 01/17 and later the maintenance is recommended to be performed 5 and 10 years after the original DOM.***
Warranty Period:	see Airtec warranty policy
Service life:	DOM prior 01.01.2017: 12.5 years from date of manufacture DOM later 01.01.2017: 15.5 years from date of manufacture