Dane aktualne na dzień: 12-11-2026 15:52

Link do produktu: https://www.sprzetspadochronowy.pl/tandem-icarus-tx2-p-230.html



Tandem Icarus TX2

Opis produktu

TX2 CHARACTERISTICS

Recommended Wing Loading: 0.67 psf - 1.61 psf

Size (Sq. Ft.)	Real Size (Sq. Ft.)	MSW (Lbs)
310	310	500
330	330	500
365	365	500

The launch of the S-Fire a few months earlier introduced the world to innovative design f
Tapes (PRT), 2nd generation of **Enhanced Ram Air Stabilizers (ERAS²)**, and **Shape**
ICARUS has integrated these elements of using the elasticity of the fabric to its' advanta
distortion and airfoil deformation, and eradicating panel flutter while simultaneously red

Consistently soft on-heading openings of 900+ feet are a feature that was at the forefro
TX2 naturally inflate from the center cell outward, which results in consistent on-heading
stretchable lines. This is a key for instructors and passengers to enjoy their experience a
year after year. We realize the importance of a comfortable reliable opening sequence e

The TX2 is incredibly reactive to control input and gives more feedback through turns wh
to the wing. There is light control line pressure, so this allows for a preferred experience

The **Reduced Drogue Loading System** is one of the highlights of this system. It is an
the drogue, while bypassing the canopy structure itself. Two lines routed through the ca
central suspension lines, which avoids stressing the canopy fabric during deployment. Le
the drogue attachment point results in more durability and decreased canopy weight an

The TX2 was created through a 3D planform design, and doesn't fall short with regards t
the crossport reinforcements and the change in the line set configuration due to the ERA
TX2 is available in the standard 6&2 Brake Configuration without a brake setting, which

The TX2 is clearly the reliable, durable and superior choice for your operation.